

2018 OUTLANDER™ MAX PRO 1000 T3

HIGHLIGHTS

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Extra Low L gear
- Tri-Mode Dynamic Power Steering (DPS™)
- Torsional Trailing arm Independent rear suspension (TTI)
- Increased ground clearance
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle[†] ACT HD radial tires
- Relocated air intakes
- 1,361 kg WARN[‡] winch with roller fairlead
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards
- 21.4 L water-resistant rear compartment



ENGINES	1000
Type	Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE [†] auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with increased suspension pre-load 22.9 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) with increased suspension pre-load 23.6 cm travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	1,361 kg WARN winch with roller fairlead	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
T3 features	Seat with backrest, lockable fuel cap, transmission lockable in park mode (P), towing hitch and trailer plug, two front position lamps + directional indicators, extra tail light / brake light + directional indicators, mirrors, horn	Seat	Seat with backrest
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

WARRANTY	
Factory	2 years
Extended	Up to 36 months B.E.S.T. coverage

TIRES / WHEELS	
Front Tires	Carlisle [†] ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle [†] ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES	
L x W x H	238.8 x 116.8 x 135 cm
Wheelbase	149.9 cm
Ground Clearance	30.5 cm
Seat Height	87.7 cm
Dry Weight*	374 kg
Rack Capacity	Front: 45 kg Rear: 90 kg
Storage Capacity	Rear: 21.4 L
Towing Capacity	750 kg trailer with brakes and 590 kg trailer without brakes
Fuel Capacity	20.5 L

BEST PROTECTION ©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US, Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GMV Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.



Can-AmOffroad.com

